Veria Flexicable 20

Technical specifications:

Cable thickness: 7mmCold tail: 2.3m

Cable shape: Oval-shaped

Pulling strenght: 120NmDeformation strenght: 2000Nm

SolutionSolutionSolutionSolutionSolutionPEX

Screen: 16 x 0,3mm Cu

Outer sheath:
PVC

Output pr. m:
20W/m at 230V

Cable colour: Yellow
 Warrant: 12 years
 Max. temparature: 80°C
 Certified by: Semko



Product range:

	Lenght:	100W/m² (C-C = 20 cm)	150W/m² (C-C = 13,3 cm)	200W/m² (C-C = 10 cm)
Veria Flexicable 20, 197W	10m	2,0m²	1,3m²	1,0m²
Veria Flexicable 20, 425W	20m	4,0m²	2,7m²	2,0m²
Veria Flexicable 20, 650W	32m	6,4m²	4,0m²	3,0m²
Veria Flexicable 20, 850W	40m	8,0m²	5,3m²	4,0m²
Veria Flexicable 20, 970W	50m	10,0m²	6,7m²	5,0m²
Veria Flexicable 20, 1267W	60m	12,0m²	8,0m²	6,0m²
Veria Flexicable 20, 1415W	70m	14,0m²	9,3m²	7,0m²
Veria Flexicable 20, 1625W	80m	16,0m²	10,7m²	8,0m²
Veria Flexicable 20, 1896W	90m	18,0m²	12,0m²	9,0m²
Veria Flexicable 20, 1974W	100m	20,0m²	13,3m²	10,0m²
Veria Flexicable 20, 2534W	125m	25,0m²	16,7m²	12,5m²

